

Configuration routeur

Building configuration...

Current configuration : 2513 bytes

!

! Last configuration change at 07:18:03 UTC Fri Apr 5 2024

!

version 15.4

service timestamps debug datetime msec

service timestamps log datetime msec

no service password-encryption

!

hostname Router

!

boot-start-marker

boot-end-marker

!

!

!

no aaa new-model

!

!

!

!

!

!

!

!

!

!

!

!

!

!

ip cef

no ipv6 cef

multilink bundle-name authenticated

!

cts logging verbose

!

!

license udi pid CISCO1921/K9 sn FCZ2150408F

!

!

!

redundancy

```
!  
!  
controller VDSL 0/0/0  
!  
!  
!  
!  
!  
interface Embedded-Service-Engine0/0  
  no ip address  
  shutdown  
!  
interface GigabitEthernet0/0  
  no ip address  
  duplex auto  
  speed auto  
!  
interface GigabitEthernet0/0.10  
  encapsulation dot1Q 10  
  ip address 172.20.0.1 255.255.255.0  
  ip helper-address 172.20.0.10  
  ip nat inside  
  ip virtual-reassembly in  
!  
interface GigabitEthernet0/0.20  
  encapsulation dot1Q 20  
  ip address 172.20.20.1 255.255.255.0  
  ip helper-address 172.20.0.10  
  ip nat inside  
  ip virtual-reassembly in  
!  
interface GigabitEthernet0/0.30  
  encapsulation dot1Q 30  
  ip address 172.20.30.1 255.255.255.0  
  ip helper-address 172.20.0.10  
  ip nat inside  
  ip virtual-reassembly in  
!  
interface GigabitEthernet0/0.40  
  encapsulation dot1Q 40  
  ip address 172.20.40.1 255.255.255.0  
  ip helper-address 172.20.0.10  
  ip nat inside  
  ip virtual-reassembly in  
!  
interface GigabitEthernet0/0.50  
  encapsulation dot1Q 50  
  ip address 172.20.50.1 255.255.255.0
```

```
ip helper-address 172.20.0.10
ip nat inside
ip virtual-reassembly in
!
interface GigabitEthernet0/1
ip address 10.0.0.2 255.255.255.0
ip nat outside
ip virtual-reassembly in
duplex auto
speed auto
!
interface ATM0/0/0
no ip address
shutdown
no atm ilmi-keepalive
!
interface Ethernet0/0/0
no ip address
shutdown
!
ip forward-protocol nd
!
no ip http server
no ip http secure-server
!
ip nat inside source list 10 interface GigabitEthernet0/1 overload
ip nat inside source list 20 interface GigabitEthernet0/1 overload
ip nat inside source list 30 interface GigabitEthernet0/1 overload
ip nat inside source list 40 interface GigabitEthernet0/1 overload
ip route 0.0.0.0 0.0.0.0 10.0.0.1
!
!
!
access-list 10 permit 172.20.0.0 0.0.0.255
access-list 20 permit 172.20.20.0 0.0.0.255
access-list 30 permit 172.20.30.0 0.0.0.255
access-list 40 permit 172.20.40.0 0.0.0.255
!
control-plane
!
!
!
line con 0
line aux 0
line 2
no activation-character
no exec
transport preferred none
```

```
transport output pad telnet rlogin lapb-ta mop udptn v120 ssh
stopbits 1
line vty 0 4
login
transport input none
!
scheduler allocate 20000 1000
!
end
```