

Configuration de la borne WIFI

Building configuration...

Current configuration : 1919 bytes

```
!  
version 12.3  
no service pad  
service timestamps debug datetime msec  
service timestamps log datetime msec  
service password-encryption  
!  
hostname ap  
!  
enable secret 5 $1$MDd7$pn2gIRypv.62c6APPNKx3/  
!  
ip subnet-zero  
!  
!  
no aaa new-model  
!  
dot11 ssid WiFi-Stade-YAHL  
    authentication open  
    authentication key-management wpa  
    guest-mode  
    wpa-psk ascii 7 072D355F1C594B5153  
!  
power inline negotiation prestandard source  
!  
!  
username Cisco password 7 1531021F0725  
!  
bridge irb  
!  
!  
interface Dot11Radio0  
    no ip address  
    no ip route-cache  
    !  
    encryption mode ciphers aes-ccm tkip  
    !  
    ssid WiFi-Stade-YAHL  
    !  
    speed basic-1.0 basic-2.0 basic-5.5 6.0 9.0 basic-11.0 12.0 18.0 24.0 36.0 48.0 54.0  
    station-role root  
    bridge-group 1  
    bridge-group 1 subscriber-loop-control
```

```
bridge-group 1 block-unknown-source
no bridge-group 1 source-learning
no bridge-group 1 unicast-flooding
bridge-group 1 spanning-disabled
!
interface Dot11Radio1
no ip address
no ip route-cache
shutdown
speed basic-6.0 9.0 basic-12.0 18.0 basic-24.0 36.0 48.0 54.0
station-role root
bridge-group 1
bridge-group 1 subscriber-loop-control
bridge-group 1 block-unknown-source
no bridge-group 1 source-learning
no bridge-group 1 unicast-flooding
bridge-group 1 spanning-disabled
!
interface FastEthernet0
no ip address
no ip route-cache
duplex auto
speed auto
bridge-group 1
no bridge-group 1 source-learning
bridge-group 1 spanning-disabled
!
interface BVI1
ip address 172.20.30.2 255.255.255.0
no ip route-cache
!
ip http server
no ip http secure-server
ip http help-path http://www.cisco.com/warp/public/779/smbiz/prodconfig/help/eag
!
!
control-plane
!
bridge 1 route ip
!
!
!
line con 0
transport preferred all
transport output all
line vty 0 4
login local
transport preferred all
```

REBAS Yanis,

Asmaa,

Halima,

Loïc

```
transport input all
transport output all
line vty 5 15
login
transport preferred all
transport input all
transport output all
!
end
```